Energy Efficiency Design Summary

(Part 9 Residential)

This form to be completed & signed by the person who reviews and takes responsibility for the energy efficiency design of the project Information on completing this form is contained on the reverse

	Intorm	nation on c	ompleting this	form is contained on the	reverse		
For use by Principal Authority							
Application No				Model/Certification Number			
A. Project Information	DAMES OF PAR				History and the second		
A. Project information Building number, street name Unit number							
Municipality Pos			code	Reg. Plan number / other desc	ription		
B. Compliance Option							
☐ SB-12 Prescriptive [SB-12		Table:	Package:				
☐ SB-12 Performance* [SB-12 - 2.1.2.]			* Attach en	* Attach energy performance calculations using an approved software			
☐ Energy Star®* [SB-12 - 2.1		* Attach BOP form. House must be labeled on completion by Energy Star					
☐ EnerGuide 80® *		* House mu	* House must be evaluated by NRCan advisor and meet a rating of 80				
C. Project Design Conditions							
limatic Zone (SB-1): Heating Equipmer			nt Efficiency	Space Heating Fuel	Source		
□ Zone 1 (< 5000 degree days)	□ ≥ 90%			□ Gas	□ Propane	□ Solid Fuel	
⊐ Zone 2 (≥ 5000 degree days) ☐ ≥ 78% < 90%			FUE	□ Oil	□ Electric	□ Earth Energy	
Vindows+Skylights+Glass Doors				Other Building Conditions			
Gross Wall Area = m ²	% Windows+		%	☐ ICF Basement	□ Walkout Baseme	nt □ Log/Post&Beam	
Gross Window+ Area = m ⁻				□ ICF Above Grade	□ Slab-on-ground		
D. Building Specifications							
Building Component RSI / R values				Building Con	ponent	Efficiency Ratings	
Thermal Insulation				Windows & Doors			
Ceiling with Attic Space				Vindows/Sliding Glass Doors			
eiling without Attic Space				Skylights			
Exposed Floor				Mechanicals			
Walls Above Grade				Space Heating Equip. ²			
Basement Walls				HRV Efficiency (%)			
Slab (all >600mm below grade)				DHW Heater (EF)			
Slab (edge only ≤600mm below grade)				NOTES 1. Provide U-Value in W/m2.K, or ER rating			
Slab (all ≤600mm below grade, or heated)				Provide U-Value in Wima.K, of ER failing Provide AFUE or indicate if condensing type combined system used			
E. Performance Design \	/erificat	tion [com	olete applicable	sections if SB-12 Performa	nce, Energy Star or En	erGuide80 options used]	
SB-12 Performance:							
The annual energy consumption using Subsection 2.1.1. SB-12 Package isGj (1 Gj =1000Mj)							
The annual energy consumption of this house as designed isGj							
The software used to simulate the annual energy use of the building is: air changes per hour @50Pa.							
Energy Star. BOP form attached. The house will be labeled on completion by:							
Energy Star and EnerGuide80: Evaluator/Advisor/Rater Name: Evaluator/Advisor/Rater Licence #:							
Evaluator/Advisor/Rater Name: Evaluator/Advisor/Rater Licence #:							
F. Declaration [by the person who reviews and takes responsibility for the energy efficiency design]							
I certify that I have reviewed the design documents submitted with the permit application, that the information contained on this form is consistent with the							
design documents, and that information used in any annual energy use calculations, if applicable, is a true representation of the design documents.							
Name Signature Date:							

Guide to the Energy Efficiency Design Summary Form

The Energy Efficiency Design Summary form summarizes the compliance path used by a house designer to comply with energy efficiency requirements of the Ontario Building Code. This form is completed by the person responsible for the energy efficiency design of the project, and must be submitted with the building permit application. The information on this form MUST reflect the drawings and specifications being submitted, or the building permit will be refused. Refer to Supplementary Standard SB-12 for details about building code compliance requirements. Further information about energy efficiency requirements for new buildings is available from the provincial building code website at www.mah.gov.on.ca, or the municipal building department.

Beginning January 1, 2012, a house designer must use one of four energy efficiency compliance options in the building code:

- 1. Comply with the SB-12 Prescriptive design tables,
- 2. Use the SB-12 Performance compliance method, and model the design against the prescriptive standards,
- 3. Design to Energy Star standards, or
- 4. Evaluate the design according to *EnerGuide* technical procedures and achieve a rating of 80 or more.

COMPLETING THE FORM

B. Compliance Options

Indicate the compliance option being used.

- <u>SB-12 Prescriptive</u> requires that the building conforms to a package of thermal insulation, window and mechanical system efficiency requirements set out in Subsection 2.1.1. of SB-12. Energy efficiency design modeling and testing of the building is not required under this option.
- <u>SB-12 Performance</u> refers to the alternative method of compliance set out in Subsection 2.1.2. of SB-12. Using this approach the designer must use recognized energy simulation software (HOT2000 V9.34c1.2 or newer), and submit documents which show that the annual energy use of the building is equal to a prescriptive package.
- <u>Energy Star</u> houses must be designed to <u>Energy Star</u> requirements and be labelled on completion by Energuality or other agency. The <u>Energy Star</u> BOP form must be submitted with the permit documents.
- <u>EnerGuide80</u> houses are validated by NRCan authorized energy advisors and must achieve a rating of 80 or more when evaluated in accordance with EnerGuide administrative and technical procedures.

C. Project Design Conditions

Climatic Zone: The number of degree days for Ontario cities is contained in Supplementary Standard SB-1 Windows, Skylights and Glass Doors: If the ratio of the total gross area of windows, sidelights, skylights and glass doors to the total gross area of walls is more than 17%, higher efficiency glazing is required. If the ratio is more than 22% the <u>SB-12 Prescriptive</u> option may not be used. The total area is the sum of all the structural rough openings. Some exceptions apply. Refer to 2.1.1.1. of SB-12 for further details. Fuel Source and Heating Equipment Efficiency: The fuel source and efficiency of the proposed heating equipment must be specified in order to determine which <u>SB-12 Prescriptive</u> compliance package table applies.

D. Building Specifications

Thermal Insulation: Indicate the RSI or R-value being proposed where they apply to the house design. Under the <u>SB-12 Prescriptive</u> option, RSI 3.52 wall insulation is permitted in certain conditions where other design elements meet higher standards. Refer to SB-12 for further details.

Other Building Conditions: These construction conditions affect SB-12 Prescriptive compliance requirements.

E. Performance Design Summary

This section is not required to be completed if the <u>SB-12 Prescriptive</u> option is being used.

AIRTIGHTNESS REQUIREMENTS FOR NEW HOUSES

All houses must comply with increased air barrier requirements in the building code. Notice of air barrier completion must be provided and an inspection conducted prior to it being covered. A blower door test to verify the air tightness of the house must be conducted during construction if the <u>NRCan EnerGuide80</u> option is used, or if the <u>SB-12 Performance</u> or <u>Energy Star</u> options are used and an air tightness of less than 2.5 ACH @ 50 Pa in the case of detached houses, or 3.0 ACH @ 50 Pa in the case of attached houses is necessary to meet the required energy efficiency standard.

ENERGY EFFICIENCY LABELING FOR NEW HOUSES

Energy Star and EnerGuide issue labels for new homes constructed under their energy efficiency programs. The building code does not regulate new home labelling.